

CDXconventional

# CCP-E

## CONVENTIONAL MANUAL CALL POINT

### Features

- ▶ Approved to EN54-11:2001
- ▶ Terminals can accommodate up to a 2.5 mm<sup>2</sup> solid conductor
- ▶ Other colours available on request
- ▶ Approved by LPCB



**AQL**  
PROTECCION. S.A.

**ANBER**



### Description

The CCP-E is a Conventional call-point based upon the industry standard KAC world series housing and features easy to install, push-fit wiring terminals.

The unit can support either a 'Frangible Glass' element or a 'Non Frangible Plastic' element.

## Specification

Ordering codes	CCP-E
Nominal operating resistance	470 Ω
Maximum contact resistance (R)	200 Ω
Ingress Protection Rating	IP24
Operating Temperature Range	-10 °C to 55 °C
Storage Temperature Range	-10 °C to 55 °C
Maximum Humidity	95%RH - Non condensing (at 40 °C)
Colour / Case Material	Red / Blue / ABS
Weight (g) / Dimensions (mm)	(Flush Mount) 110 / W89 x H93 x D27.5 (Surface Mount with Back Box) 161 / W89 x H93 x D59.5
Accessories	Frangible Element      KAC/G/HE Non-Frangible Element      KAC/EWS/HE