





Intelligent Wall Sounder Mounting Base

Features

- ▶ Electronics free
- > Stainless steel contacts
- ▶ Takes 2.5 mm² cables
- ▶ Slim profile only 13 mm
- Rugged wiring contacts
- ▶ Quick Connection via square cable clamps
- ▶ Also available in white.



Description

 $\label{lem:model YBO-R/3} \ \text{Model YBO-R/3} \ \text{is a Sounder Mounting Base, which is fully compatible with}$ Hochiki's ESP range of sensors and designed specifically for the Hochiki range of wall sounders, the CHQ-WS2 Wall Sounder and the CHQ-WSB2 Wall Sounder Beacon.

It is supplied with square cable clamps for secure and reliable cable termination.

Specification	
Operating Temperature Range	-10 °C to +50 °C
Storage Temperature Range	-30 °C to + 70 °C
Maximum Humidity	95% RH - Non Condensing (at 40 °C)
Colour / Material	Red or White / ABS
Weight (g) / Diameter (mm) / Height (mm)	60 / 100 / 13
Fixing Centres (mm)	Beam Head ± 0.3 ° Reflector ± 2 ° (static not auto-aligning)
Alarm Sensitivity Levels	48 ~ 74
Maximum Wire Thickness	2.5 mm² Cables

Ordering Codes

Product Part Number

YBO-R/3(RED) Wall Sounder Mounting Base (Red)

YBO-R/3(WHT) Wall Sounder Mounting Base (White)









