

Powered Output Module

CHQ-POM



Features

- ▶ Supplies 24 VDC. at various current levels, 2 mA to 32 mA in increments of 2 mA
- ▶ User-selectable current output
- ▶ Includes two monitored inputs
- ▶ Small design, provides simple connectivity to ESP loop for third-party devices, such as IFD-E
- ▶ Colour-coded flying leads for simple installation

Description

Model CHQ-POM is a powered-output module designed to supply 24 VDC at various, user-selectable current levels from 2 to 32 mA (in increments of 2 mA). The unit is small enough to be added to other third-party devices thereby allowing a range of equipment to be added to the ESP loop. The unit also features two monitored inputs.

Specification		
Ordering code	CHQ-POM	
Operating voltage	17 – 31 VDC	
Quiescent Current	200 μ A (at 41 V)	
Alarm Current	2.3 ~ 32.3 mA	
Test Signal Voltage	14 to 30 VDC	
Input Ratings	Open Circuit	>100 k Ω
	Normal State	~10 k Ω (resistor provided)
	Input Activation	~470 Ω (resistor provided)
	Short Circuit	<50 Ω
Operating temperature range	-10 $^{\circ}$ C to + 50 $^{\circ}$ C	
Storage temperature range	-30 $^{\circ}$ C to + 60 $^{\circ}$ C	
Maximum humidity	95% RH - Non condensing (at 40 $^{\circ}$ C)	
Colour / Case Material	Ivory / ACS	
Weight (g) / Length / Width / Depth (mm)	30 / 65 / 42 / 19	