

Conventional Weatherproof Manual Call Point

CCP-W



Features

- ▶ Approved to EN54-11:2001
- ▶ Terminals can accommodate up to a 2.5 mm² solid conductor.
- ▶ Other colours available on request
- ▶ Ingress Protection rated to IP67
- ▶ Approved by LPCB

Description

The CCP-W is a Conventional call-point based upon the industry standard KAC world series housing and features easy to install, push-fit wiring terminals.

The unit can support either a 'Frangible Glass' element or a 'Non Frangible Plastic' element and features a weatherproof Housing to IP67, which means it can be mounted in the most severe environmental conditions without water ingress.

| Specification | |
|------------------------------|-----------------------------------|
| Ordering Code | CCP-W |
| Nominal operating resistance | 470 Ω |
| Maximum contact resistance | 200 Ω |
| Ingress Protection Rating | IP67 |
| Operating Temperature Range | -25 °C to + 70 °C |
| Storage Temperature Range | -25 °C to + 70 °C |
| Maximum Humidity | 95%RH - Non condensing (at 40 °C) |
| Colour / Case Material | Red / ABS |
| Weight (g) / Dimensions (mm) | 234 / W98 x H94 x D78 |
| Accessories | Frangible Element KAC/G/HE |
| | Non-Frangible Element KAC/EWS/HE |