

Conventional Sounder Strobe

BANSHEE EXCEL LITE



Features

- ▶ Robust design
- ▶ Low current consumption
- ▶ Easy to install
- ▶ Xenon beacon technology
- ▶ Maximum 110 dB(A) at 1 m (dependent on tone selected)
- ▶ 32 user-selectable tones

Description

The BANSHEE EXCELL LITE combines the modern aesthetics of the multi-tone sounder and the very latest strobe technology to create an extremely efficient strobe/sounder combination. It is easily installed with robust terminations that can accept 2.5 mm² cables and a push and twist bayonet-fitting base.

Available in a wide choice of lens colours*, the BANSHEE EXCEL LITE will suit the majority of fire and security needs where conventional sound requires the backup of a visual alarm.

Specification		
Ordering code		BANSHEE EXCEL LITE
Operating voltage		9 – 30 V dc
Sounder current consumption (dependant on tone selected)	min	6 mA
	max	39 mA
Strobe	Current consumption	40 mA (@ 24 V dc)
	Nominal flash energy	1 W
	Flash rate	60/minute
	Lens colours available	Red/Clear*/Green*/Blue*/Amber*)
Operating Temperature Range		-20 °C to +55 °C
Maximum Sound Output (at 24 V dc) (dependant on tone selected)		110 dB(A) at 1 metre
Maximum Humidity		75%RH - Non Condensing (at 40 °C)
IP Rating		IP45

*Available upon request – please call for details